



## ABS 4W

**Controlled descent device with an automatic speed regulator -  
2 persons**

### Certification

- EN341:2011 - 1A
- ANSI Z359.4-2013

### Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication



## DESCRIPTION

ABS 4W descender with automatic speed regulation. The centrifugal force-controlled brakes keep the speed constant during the entire abseiling process and thus enable a fast and safe rescue during evacuation measures in the pendulum abseiling process of 2 persons at the same time (ABS 4W). The abseiling speed can additionally be influenced on the counter-rotating rope, with the aid of the deflection points and cable guide notch on the device.

### Variants

PRODUCT CODE	COLOR	WEIGHT	MATERIAL	COMPATIBLE ROPE DIAMETER(mm)	FINISH	NUMBER OF PERSON	WLL(Working Load Limit Kg)	Dscend Speed	FOR HEIGHT	MB S
ABS 4W	POLISH	1.7Kg	Aluminium	10.5mm	Anodised	2	200Kg	1.5m/s	200m	