

ABS 4W

Controlled descent device with an automatic speed regulator -

2 persons

Certification

- EN341:2011 1A
- ANSI Z359.4-2013

Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication



DESCRIPTION

ABS 4W descender with automatic speed regulation. The centrifugal force-controlled brakes keep the speed constant during the entire abseiling process and thus enable a fast and safe rescue during evacuation measures in the pendulum abseiling process of 2 persons at the same time (ABS 4W). The abseiling speed can additionally be influenced on the counter-rotating rope, with the aid of the deflection points and cable guide notch on the device.

Variants

| PRODUC T CODE | COLO R | WEIG HT | MATERI AL | COMPATIBLE ROPE DIAMETER(mm) | FINISH | NUMBER OF PERSON | WLL(Working Load Limit Kg) | Dscend | FOR HEIGHT | MB S |
|------------------|------------|------------|---------------|------------------------------------|--------------|------------------------|----------------------------------|--------|---------------|---------|
| ABS 4W | POLI SH | 1.7К g | Alumi nium | 10.5mm | Anodi sed | 2 | 200Kg | 1.5m/s | 200m | |