



ABS 4W

**Controlled descent device with an automatic speed regulator -
2 persons**

Certification

- EN341:2011 - 1A
- ANSI Z359.4-2013

Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication



Max. 200 kg

DESCRIPTION

ABS 4W descender with automatic speed regulation. The centrifugal force-controlled brakes keep the speed constant during the entire abseiling process and thus enable a fast and safe rescue during evacuation measures in the pendulum abseiling process of 2 persons at the same time (ABS 4W). The abseiling speed can additionally be influenced on the counter-rotating rope, with the aid of the deflection points and cable guide notch on the device.

Variants

PRODUCT CODE	COLOR	WEIGHT	MATERIAL	COMPATIBLE ROPE DIAMETER(mm)	FINISH	NUMBER OF PERSON	WLL(Working Load Limit Kg)	Dscend Speed	FOR HEIGHT	MB S
ABS 4W	POLISH	1.7Kg	Aluminium	10.5mm	Anodised	2	200Kg	1.5m/s	200m	