



BIG 8

Figure '8' descender with wings for create a locking knot

Certification

- EN 15151-2

Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



DESCRIPTION

Figure '8' descender with wings for create a locking knot. Perfect for belaying the first climber with double ropes. The large central opening allows you to overcome any knots on the ropes. It works on ropes from 9 to 16 mm Available in alu alloy and stainless steel versions

Variants

PRODU CT CODE	COLO R	WEIG HT	MATERI AL	MINIMUM ROPE DIAMETER(mm)	MAXIMUM ROPE DIAMETER(mm)	MAIN DIMENSI ON(mm)	MBS (Minimum Breaking Strength KN)	FINIS H	NUMBER OF PERSON	WLL(Worki ng Load Limit Kg)
8050 6R40 0KK	RED	260 gm	alumi nium alloy	9	16	172	30kN	ano dise d	1	140kg
8050 6P100 KK	POLI SHE	260 gm	alumi nium alloy	9	16	172	30kn	ano dise d	1	140kg
8050 6N40 0KK	BLA CK	260 gm	alumi nium alloy	9	16	172	30kn	ano dise d	1	140kg
8050 5000 0KK	POLI SH	750 gm	Stainl ess steel	9	16	172	30kn	ano dise d	1	140kg