



## Block Roll

**Single pulley with mobile side plates, low friction ball bearing, integrated blocker, designed for climbing and rescue**

### Certification

- EN 12278 :2007
- EN 567:2013

### Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



## DESCRIPTION

Single pulley with mobile side plates, low friction ball bearing, integrated blocker, designed for climbing and rescue. Suitable for the recovery of materials in a wall, conceived for the preparation of single and double hoist for rescue and self-rescue. For ropes up to 13mm diameters. The rope clamp device is tested in accordance with pt. 4.2.1 of EN 567:13 norm

## Variants

<b>PRODUCT CODE</b>	<b>COLOR</b>	<b>WEIGHT</b>	<b>BODY MATERIAL</b>	<b>WHEEL MATERIAL</b>	<b>BUSH</b>	<b>MAXIMUM ROPE DIAMETER(MM)</b>	<b>FINISH</b>	<b>MBS(MINIMUM BREAKING STRENGTH KN)</b>
81800N 000KK	BLACK/O RANGE	550g m	Aluminium alloy	Aluminium alloy	NO	13mm	Anodised	28KN