



## C Frame - PRO3 - Fixed Height / PRO 5 - Adjustable

### C frame Mobile Horizontal Rail Systems

#### Certification

- EN16415:2013

#### Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Aerospace



## DESCRIPTION

C frame Mobile Horizontal Rail Systems roll up to elevated work surfaces and provide mobile anchor points for fall protection along the length of an elevated area.

### Variants

PRODUCT CODE	PRODUCT NAME	MATERIAL	NO. OF USER	HEIGHT TO ANCHOR POINT (H)	OVERALL HEIGHT (OH)	WIDTH BETWEEN FRAME (W)	OVERALL WIDTH (OW)	LENGTH (L)	WHEELS	NO. OF RAILS	NO. OF ANCHOR
70033	PRO3 Fixed Height	Rail and support structure: Extruded 6061-T6 Aluminum Base Connectors and Wheel Assemblies: Mild Steel Tube & Plate Trolley Body: Zinc-Plated Steel or 304 Stainless Steel Trolley Wheels: Nyla Tron GSM Bearing Grade Nylon Hardware: Grade 5 Grade 8 Zinc-Plated Finish (aluminum): Safety Orange powder coat / Mill Finish Finish (Zinc): CS-500 (Type II SC-2 ASTM B633-85)	-	7.7m (305 inch)	8.15 m (321 inch)	2.7 m (108 inch)	3.2 m (126 inch)	4.8 m (192 inch)	Rubber Moulded	1	2

5009	PRO3 Fixed Height	-	-	6.1m (241 inch)	6.4m (252 inch)	4.5m (180 inch)	5m (198 inch)	4.8m (192 inch)	Rubber Molded	1	2
70382	PRO3 Fixed Height	-	-	5.8m (228 Inch)	6.6m (260 inch)	6m (240 inch)	6.47m (255 inch)	5.4m (213 inch)	Urethane	1	2
50007	PRO5 Adjustable	Rail and support structure: Extruded 6061-T6 Aluminum Base Connectors and Wheel Assemblies: Mild Steel Tube & Plate Trolley Body: Zinc-Plated Steel or 304 Stainless Steel Trolley Wheels: Nyla Tron GSM Bearing Grade Nylon Hardware: Grade 5 Grade 8 Zinc-Plated Finish (aluminum): Safety Orange powder coat / Mill Finish Finish (Zinc): CS-500 (Type II SC-2 ASTM B633-85)	-	3.76m (148inch) to 5.6m (222inch)	4.2m (164inch) to 6m (238inch)	2.9m (114 inch)	3.65m (144 inch)	4.8m (192 inch)	Rubber Molded	1	1

5004	PRO5 Adjustable	-	-	6.0m (240 inch) to 10.3m (405 inch)	6.7m (263 inch) to 10.9m (429 inch)	4.5m (180 inch)	5m (198 inch)	4.8m (192 inch)	Rubber Molded	2	2
70381	PRO5 Adjustable	-	-	5.7m (219 inch) to 10m (395 inch)	6.3m (248 inch) to 8.8m (347 inch)	6m (240 inch)	6.47m (255 inch)	5.4m (214 inch)	Urethane	1	2