



C Frame - PRO3 - Fixed Height / PRO 5 - Adjustable

C frame Mobile Horizontal Rail Systems

Certification

- EN16415:2013

Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Aerospace



DESCRIPTION

C frame Mobile Horizontal Rail Systems roll up to elevated work surfaces and provide mobile anchor points for fall protection along the length of an elevated area.

Variants

PRO DUC T COD E	PRO DUC T NAM E	MATERIAL	NO. OF USE R	HEIGH T TO ANCH OR POINT (H)	OVERA LL HEIGH T (OH)	WIDT H BETW EEN FRAM E (W)	OVER ALL WIDT H (OW)	LEN GTH (L)	WHE ELS	NO. OF RAIL S	NO. OF ANC HOR
70 03 3	PR O 3 Fix ed Hei ght	Rail and support structure: Extruded 6061-T6 Aluminum Base Connectors and Wheel Assemblies: Mild Steel Tube & Plate Trolley Body: Zinc-Plated Steel or 304 Stainless Steel Trolley Wheels: Nyla Tron GSM Bearing Grade Nylon Hardware: Grade 5 Grade 8 Zinc-Plated Finish (aluminum): Safety Orange powder coat / Mill Finish Finish (Zinc): CS-500 (Type II SC-2 ASTM B633-85)	-	7.7m (305 inch)	8.15 m (321 inch)	2.7 m (108 inch)	3.2 m (12 6 inc h)	4.8 m (19 2 inc h)	Ru bb er Mo lde d	1	2

5009	PRO3 Fixed Height	-	-	6.1m (241 inch)	6.4m (252 inch)	4.5m (180 inch)	5m (198 inch)	4.8m (192 inch)	Rubber Molded	1	2
70382	PRO3 Fixed Height	-	-	5.8m (228 Inch)	6.6m (260 inch)	6m (240 inch)	6.47m (255 inch)	5.4m (213 inch)	Urethane	1	2
50007	PRO5 Adjustable	Rail and support structure: Extruded 6061-T6 Aluminum Base Connectors and Wheel Assemblies: Mild Steel Tube & Plate Trolley Body: Zinc-Plated Steel or 304 Stainless Steel Trolley Wheels: Nyla Tron GSM Bearing Grade Nylon Hardware: Grade 5 Grade 8 Zinc-Plated Finish (aluminum): Safety Orange powder coat / Mill Finish Finish (Zinc): CS-500 (Type II SC-2 ASTM B633-85)	-	3.76m (148inch) to 5.6m (222inch)	4.2m (164inch) to 6m (238inch)	2.9m (114 inch)	3.65m (144 inch)	4.8m (192 inch)	Rubber Molded	1	1

50 04	PR O5 Adj ust abl e	-	-	6.0m (240 inch) to 10.3 m (405i nch)	6.7m (263 inch) to 10.9 m (429i nch)	4.5 m (180 inch)	5m (19 8 Inc h)	4.8 m (19 2 inc h)	Ru bb er Mo lde d	2	2
70 38 1	PR O 5 Adj ust abl e	-	-	5.7m (219i nch) to 10m (395i nch)	6.3m (248i nch) to 8.8m (347i nch)	6m (240 inch)	6.4 7m (25 5 inc h)	5.4 m (21 4 inc h)	Ur eth an e	1	2