

EXTRA ROLL

Aluminum pulley with single wheel, Equipped with two attachment points for use in complex lifting systems.

Certification

- EN 12278:2007 Industry Type
 - Tactical
 - Oil and Gas/Mining
 - Chemical and Pharma
 - Fire and Disaster Mgmt
 - Government Departments
 - Railways
 - Metals and Cement
 - Manufacturing
 - Construction
 - Adventure Parks and Hospitality
 - Aerospace
 - Telecommunication
 - Arboriculture



DESCRIPTION

Aluminum pulley with single wheel, mobile side plates and high efficiency (96%) ball bearing . Equipped with two attachment points for use in complex lifting systems. For ropes up to 13 mm diameter.

Variants

PRODUC T CODE	COLOR	WEIG HT	BODY MATERIA L	WHEEL MATERIA L	MAXIMUM ROPE DIAMETER(m m)	EFFICI ENCY	BALL BEARIN G	BUS H	FINISH	MBS(Minimum Breaking Strength)
82000 OP00K k	Orang e	260 gm	Alumini um alloy	Aluminiu m alloy	13mm	0.96	YES	NO	Anod ised	30KN
82001P N00KK	Black/ Polis	235 gm	Alumini um alloy	Nylon	13mm	0.96	YES	NO	Anod ised	30KN
82000 NP00K K	Black	245 gm	Alumini um alloy	Aluminiu m alloy	13mm	0.96	YES	NO	Anod ised	30KN