



## EXTRA ROLL

**Aluminum pulley with single wheel, Equipped with two attachment points for use in complex lifting systems.**

### Certification

- EN 12278:2007

### Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



## DESCRIPTION

Aluminum pulley with single wheel, mobile side plates and high efficiency (96%) ball bearing . Equipped with two attachment points for use in complex lifting systems. For ropes up to 13 mm diameter.

### Variants

PRODUCT CODE	COLOR	WEIGHT	BODY MATERIAL	WHEEL MATERIAL	MAXIMUM ROPE DIAMETER(m)	EFFICIENCY	BALL BEARING	BUSH	FINISH	MBS(Minimum Breaking Strength)
82000 OP00Kk	Orange	260 gm	Aluminum alloy	Aluminum alloy	13mm	0.96	YES	NO	Anodised	30KN
82001P N00KK	Black/Polis	235 gm	Aluminum alloy	Nylon	13mm	0.96	YES	NO	Anodised	30KN
82000 NP00KK	Black	245 gm	Aluminum alloy	Aluminum alloy	13mm	0.96	YES	NO	Anodised	30KN