



## **FLOOR MOUNT CONCRETE (EXSISTING)**

**Best Hoist Permanent Base Flush Floor Mount (Existing Concrete)**

**Certification**

- EN 795:2013 EN 16415:2013

**Industry Type**

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction

## DESCRIPTION

The PRO-Series Flush Mount Base for Existing Concrete is designed to be recessed into existing concrete surface and provide a permanent support for the installation of a davit arm. Unique round plate design allows for recesses to be cut using readily available core drills, 12 diameter for the plate and 4 diameter for the sleeve tube. Large, symmetrical bolt pattern reduces the size of concrete anchor required which simplifies installation. The Base sits flush with the surrounding surface to eliminate trip any hazard and may be covered with a sleeve cap when not in use to prevent contamination. Mild Steel/CS-500 Part # 30021 Mild Steel/Hot Dip Galvanized\* Part # 30018 304 SS/Sandblasted\* Part # 30022 316 SS/Sandblasted\* Part # 30038

### Variants

| PRODUCT CODE | COLOR        | WEIGHT (gm)    | MATERIAL  | Safe working load                                 | Height                      | Reach | Entry Size |
|--------------|--------------|----------------|---|---|-----------------------------|-------|------------|
| 30018        | Steel finish | 20 lbs (9.1kg) | General Construction: Welded Steel/Stainless Steel<br>Sleeve Liner/Thrust Bearing Material: High Density Polyethylene<br>Finish Specification (Zinc): C + 343<br>Lacquer Finish Specification (Galvanized): CAN/CSA G 164 | ASTM A 123 Finish Specification (Stainless Steel) | 304 or 316):<br>Brush Blast |       |            |