



FLOOR MOUNT CONCRETE (FRESH)

Best Hoist Permanent Base Flush Floor Mount (Fresh Concrete)

Certification

- EN 795:2013 EN 16415:2013

Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction

DESCRIPTION

The PRO-Series Flush Mount base for Fresh Concrete is designed to be cast directly into concrete structures as part of new construction or renovation activity and provide a permanent support for the installation of a davit arm. The base sits flush with the surrounding surface to eliminate any trip hazard and may be covered with a sleeve cap when not in use to prevent contamination. Mild Steel/CS-500 Part # 30023 Mild Steel/Hot Dip Galvanized Part # 30043 304 SS/Sandblasted* Part # 30024 316 SS/Sandblasted* Part # 30039

Variants

PRODUCT CODE	COLOR	WEIGHT (gm)	MATERIAL	Safe working load	Height	Reach	Entry Size
30043	Steel finish	20 lbs (9.1kg)	General Construction: Welded Steel/Stainless Steel Sleeve Liner/Thrust Bearing Material: High Density Polyethylene Finish Specification (Zinc): C + 343 Lacquer Finish Specification (Galvanized): CAN/CSA G164	ASTM A 123 Finish Specification (Stainless Steel)	304 or 316): Brush Blast		