

# **GHOST**

# Multiuse device - can be used both with one or two ropes

### Certification

• EN 15151-2

## **Industry Type**

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



### **DESCRIPTION**

Ghost descender is a multiuse device. It can be used both with one or two ropes from 7.5 to 10.5 mm in diameter. It allows a dynamic belay to the leader and a selflocking belay to the second (independent if there are two seconds). It works very well for rapelling. It allows lowering and lifting manouvres simply by rotating the device. It is recomended for use with HMS connectors.

#### **Variants**

PRODU CT CODE	COLO R	WEIG HT	MATERI AL	MINIMUM ROPE DIAMETER( mm)	MAXIMUM ROPE DIAMETER( mm)	MAIN DIMENSI ON(mm)	MBS (Minimum Breaking Strength KN)	H	NUMBER OF PERSON	WLL(Worki ng Load Limit Kg)
943B 00400 KK	BLU E	65g m	Alumi nium alloy	7.5	10.5	48	-	Ano dise d	1	140Kg
943P0 0100 KK	POL ISH	65g m	Alumi num alloy	7.5	10.5	48	-	Ano dise d	1	140Kg