



## GHOST

**Multiuse device - can be used both with one or two ropes**

### **Certification**

- EN 15151-2

### **Industry Type**

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



## DESCRIPTION

Ghost descender is a multiuse device. It can be used both with one or two ropes from 7.5 to 10.5 mm in diameter. It allows a dynamic belay to the leader and a selflocking belay to the second (independent if there are two seconds). It works very well for rappelling. It allows lowering and lifting manouvres simply by rotating the device. It is recommended for use with HMS connectors.

## Variants

<b>PRODUCT CODE</b>	<b>COLOR</b>	<b>WEIGHT</b>	<b>MATERIAL</b>	<b>MINIMUM ROPE DIAMETER(mm)</b>	<b>MAXIMUM ROPE DIAMETER(mm)</b>	<b>MAIN DIMENSION(mm)</b>	<b>MBS (Minimum Breaking Strength KN)</b>	<b>FINISH</b>	<b>NUMBER OF PERSON</b>	<b>WLL(Working Load Limit Kg)</b>
943B00400KK	BLUE	65gm	Aluminium alloy	7.5	10.5	48	-	Anodised	1	140Kg
943P00100KK	POLISH	65gm	Aluminium alloy	7.5	10.5	48	-	Anodised	1	140Kg