



## GHOST

**Multiuse device - can be used both with one or two ropes**

### **Certification**

- EN 15151-2

### **Industry Type**

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



## DESCRIPTION

Ghost descender is a multiuse device. It can be used both with one or two ropes from 7.5 to 10.5 mm in diameter. It allows a dynamic belay to the leader and a selflocking belay to the second (independent if there are two seconds). It works very well for rapelling. It allows lowering and lifting manouvres simply by rotating the device. It is reccomended for use with HMS connectors.

## Variants

PRODUCT CODE	COLOR	WEIGHT	MATERIAL	MINIMUM ROPE DIAMETER(mm)	MAXIMUM ROPE DIAMETER(mm)	MAIN DIMENSION(mm)	MBS (Minimum Breaking Strength KN)	FINISH	NUMBER OF PERSON	WLL(Working Load Limit Kg)
943B00400KK	BLUE	65gm	Aluminium alloy	7.5	10.5	48	-	Anodised	1	140Kg
943P00100KK	POLISH	65gm	Aluminium alloy	7.5	10.5	48	-	Anodised	1	140Kg