



## HAS 18

**Fall arrest block / inertia reel / retractable type fall arrester with auto controlled descent**

### **Certification**

- EN - 341C:2011

### **Industry Type**

- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Aerospace



## DESCRIPTION

The HAS Auto controlled descent device range is designed for the fall protection of persons working at height, where a third party rescue is not possible or an escape rescue becomes necessary (danger due to expansion). During normal use the user can move freely the working area without having to work against a break resistance. In case of a fall, the user is safely descended at a controlled speed. Features: Nominal Load 136 Kg Proof load 170 kg Static proof load 20 kN Maximum Decent speed 0.5 M/s Tested for 1 person Aluminum Housing Steel Rope Dia 4.8 mm Descender with freewheel EN 341: 2011 1 (C)

## Variants

<b>PRODUCT CODE</b>	<b>ROPE DIAMETER</b>	<b>COLOR</b>	<b>WEIGHT(gm )</b>	<b>MATERIAL MBS (Minimum Breaking Strength KN)</b>	<b>DESCEND SPEED</b>
HAS 18	4.5mm	Polyster	11000gm	Aluminium alloy	20KN