

Pro 3 series Davit

Pro 3 series Davit system made of aluminium with variable height and reach.

Certification

• EN 795:2013 Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction



DESCRIPTION

The PRO-3 Series Hoist System is designed to provide an anchor structure for Personal Fall Arrest Systems (PFAS?s),Confined Space Entry / Retrieval and rescue equipment. Provision is made for the mounting of various winches and SRL?s to the structure on the rear of the vertical post. Other mounting options are possible using a variety of adaptor brackets available from Tuff Built Products. 1- and 2-piece Davits are available in a variety of heights to tailor a system to your specific application requirements. Upper mast referse to as upper portion of Davit which is available in various dimentions and fits to the lower mast to offer different height and reach. lower mast of Pro 3 davit is the lower or middle portion of davit which fits into the base from one end and upper mast on the other end. available in two sizes which give different height and reach to the davit system

Variants

PRODUCT CODE	COLOR	WEIGHT (gm)	MATERIAL	Safe working load	Height	Rea ch	En try Siz e
20035 (model changes with different upper and lower mast selection)	Oran ge and Silver	depen ds of model selecti on	General Construction: Extruded 6061-T6 Aluminum Brackets / Connectors: Steel / Aluminum Pulleys & Rollers: Black Acetal Hardware: Grade 5	Grade 8 Zinc-Plated Finish (aluminum): Safety Orange powder coat Mill Finish Finish (Steel): Safety Orange / Grey powder coat C + 343 Lacquer	2 people weighing not more than 141kg each.		

300104 (upper mast)	Oran ge and Silver	21lb (9.5kg s)	General Construction: Extruded 6061-T6 Aluminum	28 ft	54 ft	
NA	3001 05 (uppe r mast)	Orang e and Silver	25lb (11.4kgs)	General Construction: Extruded 6061-T6 Aluminum	28 ft	66 ft
NA	3001 06 (uppe r mast)	Orang e and Silver	31lb (14.1kgs)	General Construction: Extruded 6061-T6 Aluminum	28 ft	84 ft
NA	3001 07 (uppe r mast)	Orang e and Silver	32lb (14.5kgs)	General Construction: Extruded 6061-T6 Aluminum	28 ft	10 8 ft
NA	3001 08 (lowe r mast)	Orang e and Silver	12lb (5.4kgs)	General Construction: Extruded 6061-T6 Aluminum	40 ft	NA

NA	3001 09 (lowe r mast)	Orang e and Silver	16lb(7.3kgs)	General Construction: Extruded 6061-T6 Aluminum	52 ft	NA	
----	-----------------------------------	--------------------------	--------------	---	-------	----	--