

QUICK ROLL

Ascension handle with integrated pulley.

Certification

- EN 567
- EN 12841:2006-B UIAA

Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



DESCRIPTION

Innovative handle ascender with integrated pulley. Used in conjunction with a self-braking descender (e.g. SPARROW) it allows for ascending the work rope. Main characteristics: overmolded, ergonomic handle ascender, designed for greater efficiency when pulling and increased resistence to wear and tear; cam opening lever usable with one hand; patented system for unlocking the cam, with just one downwards movement necessary; steel cam, manufactured with technology that implements the resistance to wear and tear. Equipped with a set of teeth that protects the wear of the rope, but it is equally effective in blocking and ascending the rope. It also has three slots to prevent the accumulation of mud and reduce the effort needed to slide the device up the rope under any condition (muddy rope, frozen etc.); two attachment holes for various possible uses, anti-inversion cam system, secondary hole for connecting a quick link for an etrier.

Variants

PRODUCT CODE	COLO R	WEIG HT	MATERIA L		MAXIMUM ROPE DIAMETER(MM)	FINISH	NUMBER OF PERSON	WLL(Working Load Limit Kg)	MB S
2D663DJ(Ri ght Grip/Verson)	Oran ge	255 gm	Alumini um alloy	8mm	13mm	Anodi sed	1	140Kg	
2D663SJ(Lef t Grip/ Verson)	Gray	255 gm	Alumini um alloy	10mm	13mm	Anodi sed	1	140Kg	