



## Quad Frame

**Best Safety Systems Pro-Series Fall Arrest Quad-Frame Systems are designed to provide portable fall protection during access to and work at heights.**

### **Certification**

- EN16415:2013

### **Industry Type**

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Aerospace



## DESCRIPTION

Best Safety Systems Quad-Frames feature up to a 40 foot clear span length and 30 foot width between the uprights, and up to 24 feet of clearance below the horizontal rail(s). Some restrictions may apply to dimensions based on strength and stability considerations. Up to 4 Independent trolleys can travel the length of the rail to position anchor points directly over workers to provide for the attachment of a personal fall arrest system (PFAS)

### Variants

PRODUCT CODE	PRODUCT NAME	MATERIAL	NO. OF USER	HEIGHT TO ANCHOR POINT (H)	OVERALL HEIGHT (OH)	WIDTH BETWEEN FRAME (W)	OVERALL WIDTH (OW)	LENGTH (L)	WHEELS	NO. OF RAILS	NO. OF ANCHOR
70631	Quad Frame	Rail and support structure: Extruded 6061-T6 Aluminum Base. Connectors and Wheel Assemblies: Mild Steel Tube & Plate Trolley Body: Zinc-Plated Steel or 304 Stainless Steel Trolley Wheels: Nyla Tron GSM Bearing Grade Nylon Hardware: Grade 5/ Grade 8 Zinc-Plated Finish (aluminum): Safety Orange powder coat / Mill Finish Finish (Zinc): CS-500 (Type II SC-2 ASTM B633-85)	Maximum 4 workers at 310lbs (140kg) each	4m (158 Inch)	4.2 (168 inch)	3.4 m (134 inch)	5.8 m (229 inch)	6m (238 inch)	Rubber Molded	2	2

70 76 3	Quad Frame	-	Maximum 4 workers at 310lbs (140kg) each	4m (158 Inch )	4.2 (16 8 inch h)	3.4 m (134 inch )	4m (15 8 Inch h)	12 m (4 78 inch h)	Ru bb er Mo lde d	2	2
70 77 9	Quad Frame	-	Maximum 4 workers at 310lbs (140kg) each	5.2 m (207 Inch )	6.5 m (25 6 inch h)	5.2 m (207 inch )	5.8 m (23 0 inch h)	8.6 m (3 42 inch h)	Ru bb er Mo lde d	2	2