

Quad Frame

Best Safety Systems Pro-Series Fall Arrest Quad-Frame Systems are designed to provide portable fall protection during access to and work at heights.

Certification

• EN16415:2013

Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Aerospace



DESCRIPTION

Best Safety Systems Quad-Frames feature up to a 40 foot clear span length and 30 foot width between the uprights, and up to 24 feet of clearance below the horizontal rail(s). Some restrictions may apply to dimensions base d on strength and stability considerations. Up to 4 Independent trolleys can travel the length of the rail to position anchor points directly over workers to provide for the attachment of a personal fall arrest system (PFAS)

Variants

DUC T	PRO DUC T NAM E	MATERIAL	NO. OF USER	HEIGH T TO ANCH OR POINT (H)	OVER ALL HEIG HT (OH)	BETW	OVER ALL WIDT H	LEN GTH (L)	WHE ELS	NO. OF RAIL S	NO. OF ANC HOR
70 63 1	Qu ad Fra me	Rail and support structure: Extruded 6061-T6 Aluminum Base. Connectors and Wheel Assemblies: Mild Steel Tube & Plate Trolley Body: Zinc-Plated Steel or 304 Stainless Steel Trolley Wheels: Nyla Tron GSM Bearing Grade Nylon Hardware: Grade 5/ Grade 8 Zinc-Plated Finish (aluminum): Safety Orange powder coat / Mill Finish Finish (Zinc): CS-500 (Type II SC-2 ASTM B633-85)	Maxim um 4 worke rs at 310lb s (140k g) each	4m (158 Inch)	4.2 (16 8 inc h)	3.4 m (134 inch)	5.8 m (22 9 inc h)	6m (2 38 inc h)	Ru bb er Mo Ide d	2	2

70 76 3	Qu ad Fra me	-	Maxim um 4 worke rs at 310lb s (140k g) each	4m (158 Inch)	4.2 (16 8 inc h)	3.4 m (134 inch)	4m (15 8 Inc h)	12 m (4 78 inc h)	Ru bb er Mo lde d	2	2
70 77 9	Qu ad Fra me	-	Maxim um 4 worke rs at 310lb s (140k g) each	5.2 m (207 Inch)	6.5 m (25 6 inc h)	5.2 m (207 inch)	5.8 m (23 0 inc h)	8.6 m (3 42 inc h)	Ru bb er Mo Ide d	2	2