



RUP 503

RUP 503 is a winch equipped with clamp for mounting on tripod leg.



Certification

- EN-1469 : 2017 B

Industry Type

- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Aerospace
- Telecommunication

DESCRIPTION

RUP 503 is a winch equipped with clamp for mounting on tripod leg. The winch is equipped with six-strand steel cable with natural fibre kern, available in options of 25 m, 35 m, 45 m, 50 m in length and 6.3 mm in diameter; RUP 503 is a component of rescue equipment. Using the device, a casualty can be lifted from a lower level onto a higher level or vice-versa. The descent distance cannot be more than 2 m; With the ratio used in the mechanism it is possible to make one turn of the drum per 7.2 turns of the winch's crank; Crank arm can be disassembled for easier transport; Compatible with tripod types: TM6, TM12, TM12-2, TM13

Variants

PRODUCT CODE	LENGTH	ROPE DIAMETER	COLOR	WEIGHT	MATERIAL	WORKING LOAD
RUP 503	25 - 40 mtrs	6.3mm	Orange	7.2Kg	Hosing Aluminium Rope Galvanized Steel Wire Cable	200Kg