



## STATIC 10

**The rope is particularly designed for canyon purpose. Based on its weight/breaking strength ratio, this rope can be used in many places.**

### **Certification**

- EN 1891

### **Industry Type**

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



## DESCRIPTION

The rope is particularly designed for canyon purpose. Based on its weight/breaking strength ratio, this rope can be used in many places. This rope withstands (9) falls under EN1891 (safety requirements and testing procedures for static ropes); a static elongation of 3.5%, sheath slippage of 2% and a sheath percentage of 39. The weight of this rope is 64 g/m with an impact force of 5.2 kN (tenacity with knots, 17.8 kN).

## Variants

PRODUCT CODE	COLOR	MATERIAL	WEIGHT	ROPE DIAMETER	Static Elongation	Dynamic Elongation	IMPACT FORCE
411221	BLUE	Polyamide	49 gm/m	10 mm	0.034	-	5.4KN
411222	WHITE	Polyamide	49 gm/m	10 mm	0.034	-	5.4KN