



## STATIC 11

**The most popular semi-static rope with excellent cost performance. The rope can be widely used for sports and vertical works**

### **Certification**

- EN 1891

### **Industry Type**

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



## DESCRIPTION

11mm Static Rope is ideal for covers. During braiding, the sheath and core of this rope have been designed to minimize the slippage while providing maximum tension management to create stabilization and allowing for better balance, handling and durability. This rope withstands (16) falls under EN1891 (safety requirements and testing procedures for static ropes); a static elongation of 2.4%, sheath slippage of 4% and a sheath percentage of 34. The weight of this rope is 72 g/m with an impact force of 5.2 kN (tenacity with knots, 19.2 kN).

## Variants

<b>PRODUCT CODE</b>	<b>COLOR</b>	<b>MATERIAL</b>	<b>WEIGHT</b>	<b>ROPE DIAMETER</b>	<b>Static Elongation</b>	<b>Dynamic Elongation</b>	<b>IMPACT FORCE</b>
411241	YELLOW	Polyamide	72 gm/m	11 mm	0.024	0.34	5.8KN
411242	WHITE	Polyamide	72 gm/m	11 mm	0.024	0.34	5.8KN