



SWING ALU

Compact pulley with mobile side plates and bushings

Certification

- EN 12278:2007

Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



DESCRIPTION

The Swing Roll is a single sheave pulley with aluminum swinging side plates and nylon wheel. Taper bush lock pulley. It works with ropes up to 11mm.

Variants

PRODUCT CODE	COLOR	WEIGHT	BODY MATERIAL	WHEEL MATERIAL	MAXIMUM ROPE DIAMETER(mm)	EFFICIENCY	BALL BEARING	BUSH	FINISH	MBS(Minimum Breaking Strength)
993N00400KK	Black/Polis	120 gm	Aluminum alloy	Nylon	11mm	0.87	YES	NO	Anodised	30KN
993P00100KK	Polish	120 gm	Aluminum alloy	Nylon	11mm	0.87	YES	NO	Anodised	30KN
994000000KK	Polish	162 gm	Aluminum alloy	Nylon	11mm	0.87	YES	YES	Anodised	30KN