



TRILONGE

Braided rope Positioning lanyard designed for caving, canyoning and rescue activities.

Certification

- EN 354
- EN 566
- EN 795 / B
- EN 566



DESCRIPTION

Positioning lanyard designed for caving, canyoning and rescue activities, made of dynamic rope EN 892 10mm diameter, with sewn eyelets and rubber terminations; available in three lengths for custom arrangement of the three branches of the lanyard. - Trilonge is the factory version conform to EN 566:06, EN 354:10, EN 358:99, EN 795/B:12 norms, of a popular tool up to date handcrafted by the end user. Features: choice of 3 lengths (170 cm - 190 cm - 210 cm) depending on the needs and the user's stature. seam eyelets with a contrasting color indicator for the immediate check of the wear. lanyard lengths designed for the preparation of the 3 attachment points (short, medium, long) via Trilonge knot. rope sheath very resistant to abrasion for use in particularly aggressive environments; rubber terminals integrated for the correct and stable positioning of the connector in the sewn eyelet

Variants

PRODUCT CODE	COLOR	WEIGHT(gm)	SLING LENGTH(cm)	MATERIAL	MBS(Minimum Breking Strength KN)
279I00170KK	Black	150gm	170cm	Nylon	22KN
279I00190KK	Black	170gm	190cm	Nylon	22KN