

TRILONGE

Braided rope Positioning lanyard designed for caving, canyoning and rescue activities.

Certification

- EN 354
- EN 566
- EN 795 / B
- EN 566



DESCRIPTION

Positioning lanyard designed for caving, canyoning and rescue activities, made of dynamic rope EN 892 10mm diameter, with sewn eyelets and rubber terminations; available in three lengths for custom arrangement of the three branches of the lanyard. - Trilonge is the factory version conform to EN 566:06, EN 354:10, EN 358:99, EN 795/B:12 norms, of a popular tool up to date handcrafted by the end user. Features: choice of 3 lengths (170 cm - 190 cm - 210 cm) depending on the needs and the user?s stature. seam eyelets with a contrasting color indicator for the immediate check of the wear. lanyard lengths designed for the preparation of the 3 attachment points (short, medium, long) via Trilonge knot. rope sheath very resistant to abrasion for use in particularly aggressive environments; rubber terminals integrated for the correct and stable positioning of the connector in the sewn eyelet

Variants

| PRODUCT CODE | COLOR | WEIGHT(gm) | SLING LENGTH(cm) | MATERIAL | MBS(Minimum Breking Strength KN) |
|--------------|-------|------------|------------------|----------|----------------------------------|
| 279I00170KK | Black | 150gm | 170cm | Nylon | 22KN |
| 279I00190KK | Black | 170gm | 190cm | Nylon | 22KN |