



## TRILONGE

**Braided rope Positioning lanyard designed for caving, canyoning and rescue activities.**

### **Certification**

- EN 354
- EN 566
- EN 795 / B
- EN 566



## DESCRIPTION

Positioning lanyard designed for caving, canyoning and rescue activities, made of dynamic rope EN 892 10mm diameter, with sewn eyelets and rubber terminations; available in three lengths for custom arrangement of the three branches of the lanyard. - Trilonge is the factory version conform to EN 566:06, EN 354:10, EN 358:99, EN 795/B:12 norms, of a popular tool up to date handcrafted by the end user. Features: choice of 3 lengths (170 cm - 190 cm - 210 cm) depending on the needs and the user's stature. seam eyelets with a contrasting color indicator for the immediate check of the wear. lanyard lengths designed for the preparation of the 3 attachment points (short, medium, long) via Trilonge knot. rope sheath very resistant to abrasion for use in particularly aggressive environments; rubber terminals integrated for the correct and stable positioning of the connector in the sewn eyelet

### Variants

PRODUCT CODE	COLOR	WEIGHT(gm)	SLING LENGTH(cm)	MATERIAL	MBS(Minimum Breking Strength KN)
279I00170KK	Black	150gm	170cm	Nylon	22KN
279I00190KK	Black	170gm	190cm	Nylon	22KN