



TWIN

Aluminum pulley with double wheel, mobile side plates and high efficiency (96%) ball bearing.

Certification

- EN 12278:2007
- UIAA

Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



DESCRIPTION

Aluminum pulley with double wheel, mobile side plates and high efficiency (96%) ball bearing. Equipped with two attachment points for use in complex lifting systems. For ropes up to 13 mm diameter.

Variants

PRODUCT CODE	COLOR	WEIGHT	BODY MATERIAL	WHEEL MATERIAL	MAXIMUM ROPE DIAMETER(MM)	EFFICIENCY	BALL BEARING	BUSH	FINISH	MBS(MINIMUM BREAKING STRENGTH)
82700 OP00KK	ORANGE	490 gm	Aluminum alloy	Aluminum alloy	13mm	0.96	YES	NO	Anodised	50KN
82700 NP00KK	Black	490 gm	Aluminum alloy	Aluminum alloy	13mm	0.96	YES	NO	Anodised	50KN