



## TWIN

**Aluminum pulley with double wheel, mobile side plates and high efficiency (96%) ball bearing.**

### Certification

- EN 12278:2007
- UIAA

### Industry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



## DESCRIPTION

Aluminum pulley with double wheel, mobile side plates and high efficiency (96%) ball bearing. Equipped with two attachment points for use in complex lifting systems. For ropes up to 13 mm diameter.

### Variants

PRODUCT CODE	COLOR	WEIGHT	BODY MATERIAL	WHEEL MATERIAL	MAXIMUM ROPE DIAMETER(MM)	EFFICIENCY	BALL BEARING	BUSH	FINISH	MBS(MINIMUM BREAKING STRENGTH)
82700 OP00K K	ORANGE	490 gm	Aluminum alloy	Aluminum alloy	13mm	0.96	YES	NO	Anodised	50KN
82700 NP00K K	Black	490 gm	Aluminum alloy	Aluminum alloy	13mm	0.96	YES	NO	Anodised	50KN