

## TWIN

Aluminum pulley with double wheel, mobile side plates and high efficiency (96%) ball bearing.

Certification

- EN 12278:2007
- UIAA

Indestry Type

- Tactical
- Oil and Gas/Mining
- Chemical and Pharma
- Fire and Disaster Mgmt
- Government Departments
- Railways
- Metals and Cement
- Manufacturing
- Construction
- Adventure Parks and Hospitality
- Aerospace
- Telecommunication
- Arboriculture



## DESCRIPTION

Aluminum pulley with double wheel, mobile side plates and high efficiency (96%) ball bearing. Equipped with two attachment points for use in complex lifting systems. For ropes up to 13 mm diamete.

## Variants

PRODUC T CODE	COLOR	WEIG HT	BODY MATERIA L	WHEEL MATERIA L	MAXIMUM ROPE DIAMETER(MM )	EFFICI ENCY	BALL BEARIN G	BUS H	FINISS H	MBS(MINIMUM BREAKING STRENGTH)
82700 OP00K K	ORA NGE	490 gm	Alumini um alloy	Alumini um alloy	13mm	0.96	YES	NO	Anod ised	50KN
82700 NP00K K	Black	490 gm	Alumini um alloy	Alumini um alloy	13mm	0.96	YES	NO	Anod ised	50KN